

Bobcat 5600

Engine

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	45.5 kW
Turbocharged Engine	×
Engine Model	Bobcat D24NAP Turbo

Performance

Rated Operating Capacity (SAE)	680 kg
Operating Weight	2579 kg
Travel Speed	27.36 km/ h
Travel Speed - Max	27.4 km/ h
Travel Speed - Low	12.9 km/ h
Travel Speed - Reverse	12.9 km/ h
Machine Rated Capacity	998 kg
3- Point Hitch	n/ a

Capacities

Fuel Tank	75.7
Cargo Box Bed Load Capacity	907 kg
Cargo Box Length	1422 mm
Cargo Box Width	1295 mm
Cargo Box Height	254 mm
Cargo Box Bed Load Height	970 mm
Total Vehicle Rated Capacity	1905 kg

Hydraulic System

Auxiliary Std Flow	71.5 // min
Auxiliary Pressure	206.84 bar
Auxiliary High Flow	105.6 l/ min
Number of Tilt Cylinders	1

General

Contract Codes	Utility Machine
First Year of Production	2013

Dimension

Length	4613 mm
Length without Attachment	3691 mm
Width	1524 mm
Width (with bucket)	1575 mm
Height	2057 mm
Height with Operator Cab	2057 mm
Bed Height From Ground	970 mm
Cargo Box Maximum Load	907 kg
Cargo Box Volume	0.5 m³
Ground Clearance	235 mm
Turning Radius (AWS Mode)	2667 mm
Outside Turning Diameter	5334 mm
Wheelbase	2,235 mm

Features

Heater Air Conditioning	×
Work Lights	• • • • • • • • • • • • • • • • • • •
Enclosed Operator Cab (ROPS/ FOPS)	×

🐺 Bobcat.

Auxiliary Hydraulics	 International statements
Bob- Tach Attachment System *	• • • • • • • • • • • • • • • • • • •
Joystick Control	
Hydrostatic Transmission	•
Air Conditioning	×
Cab Enclosure	×

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.