

Engine

| | |
|----------------------|---------------------|
| Emissions Tier (EPA) | Tier 4 |
| Engine Cooling | Liquid |
| Engine Fuel | Diesel |
| Horsepower | 45.5 kW |
| Turbocharged Engine | × |
| Engine Model | Bobcat D24NAP Turbo |

Performance

| | |
|--|-------------|
| Rated Operating Capacity (SAE) | 680 kg |
| Operating Weight | 2647 kg |
| Travel Speed | 27.36 km/ h |
| Travel Speed - Max | 27.4 km/ h |
| Travel Speed - Low | 12.9 km/ h |
| Travel Speed - Reverse | 12.9 km/ h |
| Machine Rated Capacity | 998 kg |
| 3- Point Hitch | Category 1 |
| Lift Capacity at 24" behind Lift Point | 805 kg |
| Rear PTO System | Independent |
| Rear PTO - RPM | 540 |
| PTO HP | 18.6 kW |

Capacities

| | |
|------------------------------|---------|
| Fuel Tank | 75.7 l |
| Total Vehicle Rated Capacity | 1905 kg |

Hydraulic System

| | |
|--------------------------|--------------|
| Auxiliary Std Flow | 71.5 l/ min |
| Auxiliary Pressure | 206.84 bar |
| Auxiliary High Flow | 105.6 l/ min |
| Number of Tilt Cylinders | 1 |

General

| | |
|--------------------------|-----------------|
| Contract Codes | Utility Machine |
| First Year of Production | 2008 |

Dimension

| | |
|---------------------------|----------|
| Length | 4592 mm |
| Length without Attachment | 3907 mm |
| Width | 1524 mm |
| Width (with bucket) | 1575 mm |
| Height | 2057 mm |
| Height with Operator Cab | 2057 mm |
| Cargo Box Maximum Load | n/ a |
| Ground Clearance | 235 mm |
| Turning Radius (AWS Mode) | 2667 mm |
| Outside Turning Diameter | 5334 mm |
| Wheelbase | 2,235 mm |

Features

| | |
|------------------------------------|---|
| Heater Air Conditioning | ■ |
| Work Lights | ■ |
| Enclosed Operator Cab (ROPS/ FOPS) | ■ |
| Auxiliary Hydraulics | ■ |
| Bob- Tach Attachment System * | ■ |
| Joystick Control | ■ |



| | |
|--------------------------|---|
| Hydrostatic Transmission | ■ |
| Air Conditioning | ■ |
| Cab Enclosure | ■ |

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.