

Engine

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	61 hp
Turbocharged Engine	×
Engine Model	Bobcat D24NAP Turbo

Performance

Rated Operating Capacity (SAE)	1,500 lb
Operating Weight	5835 lb
Travel Speed	17 mph
Travel Speed - Max	17 mph
Travel Speed - Low	8 mph
Travel Speed - Reverse	8 mph
Machine Rated Capacity	2200 lb
3- Point Hitch	Category 1
Lift Capacity at 24" behind Lift Point	1775 lb
Rear PTO System	Independent
Rear PTO - RPM	540
PTO HP	25 hp

Capacities

Fuel Tank	20 gal
Total Vehicle Rated Capacity	4200 lb

Hydraulic System

Auxiliary Std Flow	18.9 gal/ min
Auxiliary Pressure	3,000 psi
Auxiliary High Flow	27.9 gal/ min
Number of Tilt Cylinders	1

General

Contract Codes	Utility Machine
First Year of Production	2008

Dimension

Length	180.8 in
Length without Attachment	153.8 in
Width	60 in
Width (with bucket)	62 in
Height	81 in
Height with Operator Cab	81 in
Cargo Box Maximum Load	n/ a
Ground Clearance	9.2 in
Turning Radius (AWS Mode)	105 in
Outside Turning Diameter	210 in
Wheelbase	88 in

Features

Heater Air Conditioning	■
Work Lights	■
Enclosed Operator Cab (ROPS/ FOPS)	■
Auxiliary Hydraulics	■
Bob- Tach Attachment System *	■
Joystick Control	■



Hydrostatic Transmission	■
Air Conditioning	■
Cab Enclosure	■

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.