

## Engine

Emissions Tier (EPA)	Tier 4
Engine Model	D722- E4B- BCZ-7
Engine Make	Kubota
Engine Fuel	Diesel
Maximum Governed RPM	2,500 rpm
Horsepower	13.9 hp
Gross HP	13.9 hp
Net HP	13.3 hp
Turbocharged Engine	<input type="checkbox"/>
Optional Horsepower	n/ a
Number of Cylinders	3

## Performance

Operating Weight	4,306 lb
Weight Class	2 t
Travel Speed - High	2.5 mph
Travel Speed - Low	1.5 mph
Arm Digging Force	2,086 lbf
Bucket Digging Force	4,684 lbf
Rated Lift Capacity	1023 lb
Lift Radius	118 in
Boom Swing - Left	80°
Boom Swing - Right	60°
Maximum Dig Depth	8.5 ft
Max Dump Height	8.8 ft
Maximum Reach at Ground Level	14 ft
Slew Speed	8.4 rpm
Maximum Depth of Vertical Wall	83.3 in
Ground Pressure (Rubber)	4.4 psi

## Capacities

Fuel Tank	5 gal
Hydraulic Reservoir	3.8 gal

## Hydraulic System

Auxiliary Std Flow	7.9 gal/ min
Auxiliary Pressure	2,610 psi
Number of Hydraulic Pumps	3
Pump Type	Dual outlet piston pump with gear pump
Pump Capacity	11 gal/ min

## General

Contract Codes	Excavator 316-435
First Year of Production	2014
Mainframe Model	E20 T4

## Dimension

Length	145.2 in
Overall Length in Travel Position	145.2 in
Width	39 in
Height	90.4 in
Height with Operator Cab	90.4 in
Tail Overhang, Side	0 in
Blade Width	39 in
Track Width Extended	53.5 in
Length of track on ground	49.5 in

## Features

Air Conditioning	<input type="checkbox"/>
Cab Enclosure	<input checked="" type="checkbox"/>
Cab Heater	<input checked="" type="checkbox"/>
Heater Air Conditioning	<input type="checkbox"/>
Radio	<input checked="" type="checkbox"/>
Tail Swing Type	Zero
Engine Shutdown	<input checked="" type="checkbox"/>
Auxiliary Hydraulics	<input checked="" type="checkbox"/>
Secondary Auxiliary Hydraulics	<input type="checkbox"/>
Quick Tach System	<input type="checkbox"/>
Rubber Track	<input checked="" type="checkbox"/>
Selectable Auxiliary Hydraulic Flow	<input checked="" type="checkbox"/>
Angle Blade	<input type="checkbox"/>
Suspension Seat	<input type="checkbox"/>

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.