

Engine

Emissions Tier (EPA)	Tier 4
Engine Model	D722- E4B- BCZ-7
Engine Make	Kubota
Engine Fuel	Diesel
Maximum Governed RPM	2,500 rpm
Horsepower	10.4 kW
Gross HP	10.37 kW (14.09 hp)
Net HP	9.92 kW (13.48 hp)
Turbocharged Engine	<input type="checkbox"/>
Optional Horsepower	n/ a
Number of Cylinders	3

Performance

Operating Weight	1953 kg
Weight Class	2 t
Travel Speed - High	4 km/ h
Travel Speed - Low	2.4 km/ h
Arm Digging Force	9,279 N
Bucket Digging Force	20,835 N
Rated Lift Capacity	464 kg
Lift Radius	2997 mm
Boom Swing - Left	80°
Boom Swing - Right	60°
Maximum Dig Depth	2.6 m
Max Dump Height	2.7 m
Maximum Reach at Ground Level	4.3 m
Slew Speed	8.4 rpm
Maximum Depth of Vertical Wall	2,116 mm
Ground Pressure (Rubber)	0.3 bar

Capacities

Fuel Tank	18.9 l
Hydraulic Reservoir	14.4 l

Hydraulic System

Auxiliary Std Flow	29.9 l/ min
Auxiliary Pressure	179.95 bar
Number of Hydraulic Pumps	3
Pump Type	Dual outlet piston pump with gear pump
Pump Capacity	41.64 l/ min

General

Contract Codes	Excavator 316-435
First Year of Production	2014
Mainframe Model	E20 T4

Dimension

Length	3688 mm
Overall Length in Travel Position	3688 mm
Width	991 mm
Height	2296 mm
Height with Operator Cab	2296 mm
Tail Overhang, Side	0 mm
Blade Width	990.6 mm
Track Width Extended	1,359 mm
Length of track on ground	1,257 mm

Features

Air Conditioning	<input type="checkbox"/>
Cab Enclosure	<input checked="" type="checkbox"/>
Cab Heater	<input checked="" type="checkbox"/>
Heater Air Conditioning	<input type="checkbox"/>
Radio	<input checked="" type="checkbox"/>
Tail Swing Type	Zero
Engine Shutdown	<input checked="" type="checkbox"/>
Auxiliary Hydraulics	<input checked="" type="checkbox"/>
Secondary Auxiliary Hydraulics	<input type="checkbox"/>
Quick Tach System	<input type="checkbox"/>
Rubber Track	<input checked="" type="checkbox"/>
Selectable Auxiliary Hydraulic Flow	<input checked="" type="checkbox"/>
Angle Blade	<input type="checkbox"/>
Suspension Seat	<input type="checkbox"/>

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.