

Engine

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	45.6 kW
Turbocharged Engine	×
Engine Model	2.4L Bobcat Engine
Engine Make	Bobcat
Displacement	2,393 cm ³
Torque RPM	1,800 rpm
Number of Cylinders	4

Performance

Rated Operating Capacity (SAE)	635 kg
Operating Capacity (50% of Tip)	907 kg
Rated Operating Capacity (35% Of Tip)	635 kg
Tipping Load	1814 kg
Operating Weight	2789 kg
Travel Speed	11.7 km/ h
Travel Speed (2- speed option)	17.7 km/ h
Ground Pressure (Rubber)	0.32 bar

Capacities

Fuel Tank	65.5 l
-----------	--------

Hydraulic System

System Relief @ Quick Couplers	227.53 bar
Auxiliary Std Flow	63.2 l/ min
Auxiliary High Flow	n/ a

General

Contract Codes	Compact Track Loader
----------------	----------------------

Controls

Hydraulic (Lift and Tilt)	Dual Pedals
Auxiliary Hydraulics Type	Finger Tip Controls

Dimension

Length	2499 mm
Length without Attachment	2499 mm
Length with Standard Bucket	3216 mm
Width	1397 mm
Width (with bucket)	1422 mm
Height	1976 mm
Height with Operator Cab	1976 mm
Height to Bucket Hinge Pin	2781 mm
Reach @ Maximum Height	597 mm
Turning Radius	1979 mm
Length of track on ground	1275 mm
Track Width	300 mm
Ground Clearance	213.36 mm
Dump Angle @ Maximum Height	40°

Features

Joystick Control	×
Air Conditioning	×

Backup Alarm	■
BICS System (Interlock)	■
Cab Heater	×
Operating Lights	■
Suspension Seat	■
Two Speed Travel	×
Deluxe Instrumentation	×
Hydraulic Bucket Positioning	×
Auxiliary Hydraulics	■
Bob- Tach Attachment System *	■
Horn	■

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.