

Engine

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	61.1 hp
Turbocharged Engine	×
Engine Model	2.4L Bobcat Engine
Engine Make	Bobcat
Displacement	146 in³
Torque RPM	1,800 rpm
Number of Cylinders	4

Performance

Rated Operating Capacity (SAE)	1,400 lb
Operating Capacity (50% of Tip)	2000 lb
Rated Operating Capacity (35% Of Tip)	1400 lb
Tipping Load	4000 lb
Operating Weight	6148 lb
Travel Speed	7.3 mph
Travel Speed (2- speed option)	11 mph
Ground Pressure (Rubber)	4.7 psi

Capacities

Fuel Tank	17.3 gal
-----------	----------

Hydraulic System

System Relief @ Quick Couplers	3,300 psi
Auxiliary Std Flow	16.7 gal/ min
Auxiliary High Flow	n/ a

General

Contract Codes	Compact Track Loader
----------------	----------------------

Controls

Hydraulic (Lift and Tilt)	Dual Pedals
Auxiliary Hydraulics Type	Finger Tip Controls

Dimension

Length	98.4 in
Length without Attachment	98.4 in
Length with Standard Bucket	126.6 in
Width	55 in
Width (with bucket)	56 in
Height	77.8 in
Height with Operator Cab	77.8 in
Height to Bucket Hinge Pin	109.5 in
Reach @ Maximum Height	23.5 in
Turning Radius	77.9 in
Length of track on ground	50.2 in
Track Width	11.8 in
Ground Clearance	8.4 in
Dump Angle @ Maximum Height	40°

Features

Joystick Control	×
Air Conditioning	×

Backup Alarm	■
BICS System (Interlock)	■
Cab Heater	×
Operating Lights	■
Suspension Seat	■
Two Speed Travel	×
Deluxe Instrumentation	×
Hydraulic Bucket Positioning	×
Auxiliary Hydraulics	■
Bob- Tach Attachment System *	■
Horn	■

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.