

 SHARE

Compact Track Loaders / T870 Compact Track Loader

Specifications & Options

■ Standard
 Optional
N/A Not Applicable

Units **US**

Bobcat T870

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	100 hp
Turbocharged Engine	<input checked="" type="checkbox"/>

Performance

Rated Operating Capacity (SAE)	3,650 lb
Operating Capacity (50% of Tip)	5215 lb
Tipping Load	10430 lb
Operating Weight	12925 lb
Travel Speed	7.2 mph
Travel Speed (2-speed option)	11.4 mph
Ground Pressure (Rubber)	4.8 psi

Capacities

Fuel Tank	32.6 gal
-----------	----------

Hydraulic System

System Relief @ Quick Couplers	3,500 psi
Auxiliary Std Flow	23 gal/min
Auxiliary High Flow	36.6 gal/min

Dimension

Length	153.9 in
Length without Attachment	119.3 in
Length with Standard Bucket	153.9 in
Width	82.8 in
Width (with bucket)	84.8 in
Height	83.6 in
Height with Operator Cab	83.6 in
Height to Bucket Hinge Pin	144 in
Reach @ Maximum Height	36.5 in
Turning Radius	99 in
Length of track on ground	70.2 in
Track Width	17.7 in

Features

Joystick Control	<input checked="" type="checkbox"/>
Air Conditioning	<input type="checkbox"/>
Backup Alarm	<input type="checkbox"/>
BICS System (Interlock)	<input type="checkbox"/>
Cab Heater	<input type="checkbox"/>
Operating Lights	<input type="checkbox"/>
Suspension Seat	<input type="checkbox"/>
Two Speed Travel	<input type="checkbox"/>
Deluxe Instrumentation	<input checked="" type="checkbox"/>
Engine Shutdown	<input type="checkbox"/>
Hydraulic Bucket Positioning	<input checked="" type="checkbox"/>
High Flow Option	<input checked="" type="checkbox"/>
Auxiliary Hydraulics	<input type="checkbox"/>
Bob-Tach Attachment System	<input type="checkbox"/>
Power Bob-Tach	<input type="checkbox"/>
ACS (Switchable Controls)	N/A
Ride Control	<input checked="" type="checkbox"/>
Horn	<input type="checkbox"/>

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.