

Engine

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	74.6 kW
Turbocharged Engine	×

Performance

Rated Operating Capacity (SAE)	1599 kg
Operating Capacity (50% of Tip)	2282 kg
Tipping Load	4569 kg
Operating Weight	5863 kg
Travel Speed	11.6 km/ h
Travel Speed (2- speed option)	18.3 km/ h
Ground Pressure (Rubber)	0.34 bar

Capacities

Fuel Tank	122.3 l
-----------	---------

Hydraulic System

System Relief @ Quick Couplers	241.32 bar
Auxiliary Std Flow	87.1 l/ min
Auxiliary High Flow	138.5 l/ min

Dimension

Length	3909 mm
Length without Attachment	3030 mm
Length with Standard Bucket	3909 mm
Width	2108 mm
Width (with bucket)	2154 mm
Height	2118 mm
Height with Operator Cab	2118 mm
Height to Bucket Hinge Pin	3658 mm
Reach @ Maximum Height	927 mm
Turning Radius	2515 mm
Length of track on ground	1750 mm
Track Width	450 mm

Features

Joystick Control	×
Air Conditioning	■
Backup Alarm	■
BICS System (Interlock)	■
Cab Heater	■
Operating Lights	■
Suspension Seat	■
Two Speed Travel	■
Deluxe Instrumentation	×
Engine Shutdown	■
Hydraulic Bucket Positioning	×
High Flow Option	×
Auxiliary Hydraulics	■
Bob- Tach Attachment System *	■
Power Bob- Tach *	■
ACS (Switchable Controls)	□

Ride Control	×
Horn	■

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.