



Engine

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Displacement	55 in³
Number of Cylinders	3
Horsepower	24.8 hp

Performance

Rated Operating Capacity (ISO)	1,000 lb
Tipping Load	2898 lb
Operating Weight	3390 lb
Ground Pressure (Rubber)	5.25 psi
Travel Speed	4.1 mph
Travel Speed - Reverse	2.9 mph

Capacities

Fuel Tank	7 gal

Hydraulic System

Pump Capacity	12 gal/ min
System Relief @ Quick Couplers	2,900 psi
Auxiliary Std Flow	12 gal/ min

Dimension

Length	106.2 in
Width	35.6 in
Height	54.6 in
Height to Bucket Hinge Pin	80.9 in
Length of track on ground	41.4 in
Reach @ Maximum Height	18 6 in

Features

Lift- Arm Support	•
Auxiliary Hydraulics	•
Spark Arrestor Muffler	•
Bob- Tach Attachment System *	•
Reverse Travel Stop Panel	
Wide Track	×
Neutral Start Interlocks	•
Lift Arm Lockout With Manual Bypass	•
Tilt Lockout	•
Built- In Tie Down & Crane/ Lift Locations	
Ride- on Platform	

Compatible Attachments

Utility Fork - Loaders and Toolcat	
Utility Fork, 5 Teeth - 36"	•
Grapple, Utility - Loaders and Toolcat	
Grapple, GP - 32"	•
Grapple, Utility - 32"	•
Grapple, Industrial	
Grapple, Industrial - 36"	
Angle Broom	

01/09/2020 Page 1



52" Angle Broom	· ·
64" Angle Broom	· ·
Angle Broom - 48"	· ·
Pallet Fork	
Pallet Fork Frame- MT	· ·
Grapple, Root	
Grapple, Root - 36"	· ·
Bucket, Const./ Ind. (C/ I) - Loaders	
Mini Const./ Ind. Bucket - 36"	· ·
Auger	
Auger - 10	•
Bucket, Dirt - Loaders	
Dirt Bucket - 36"	•
Dirt Bucket - 44"	•
Bucket, General Purpose - Loaders	
General Purpose Bucket - 36"	•
General Purpose Bucket - 44"	•
General Purpose Bucket, 463 - 50"	•
Boring Unit	
Boring Unit	•
Bucket, SAL Utility	
MI BUCKET 44 SAL UTILITY	•
Digger	
Digger , 12S	•
Breaker	
Breaker, Nail Point - HB680	•
Landplane	
Landplane, Deluxe - 48"	•
Nitrogen Breaker	
MI Breaker NB140	•
Snow Blade	
Snow Blade - 54"	•
Snowblower	
Snowblower, SB150 - 36"	•
Snowblower, SB150 - 48"	•
Soil Conditioner	
Soil Conditioner, Manual - 48"	•
Stump Grinder	
Stump Grinder, SG 30	•
Sweeper	
Sweeper - 44"	•
Tiller Retory Tiller 40"	_
Rotary Tiller - 40"	•
Trencher	_
Trencher, LT112	
Trencher, LT113	•
Vibratory Plow Vibratory Plow, VP12	_
vibratory FIOW, VF 12	

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.

01/09/2020 Page 2