

Bobcat CT2535 HST

Engine

Emissions Tier (EPA)	Tier 4
Engine Make	Daedong
Horsepower	34.9 hp
Displacement	111 in³
Number of Cylinders	3
Gross HP	34.9 hp
Engine Model	3F- TM(H)4
RPM	2750

Performance

Operating Weight	3,585 lb
Travel Speed	14.4 mph
Travel Speed - Reverse	10.1 mph
3- Point Hitch	Category 1
3- pt Lift Control Type	Hydraulic Position Control System
Lift Capacity at 24" behind Lift Point	1,631 lb
Rear PTO System	Independent
Rear PTO - RPM	540
PTO HP	29.4 hp
Mid PTO - RPM	1988

Capacities

Fuel Tank	9 gal

Hydraulic System

Drive System

Number of Forward Speeds	3
Brake Type	Wet Multi Disc
Transmission Type	Infinite, 3 RangeHydrostatic
Traction System	4x4

General

Contract Codes	Compact Utility Tractor
First Year of Production	2019

Dimension

Length	120.9 in
Width	64 in
Height	91 in
Ground Clearance	12.3 in
Turning Radius	8' 9"
Wheelbase	5' 5"
Front Tire Size	Front AG. (TURF, INDUSTRIAL)7-16 (28 x 8.5-15/6, 27X8.5-15)
Rear Tire Size	Rear AG. (TURF, INDUSTRIAL)11.2-24 (41 x 14-20/4, 15-19.5)

Features

Suspension Seat	
Spark Arrestor Muffler	Standard
Tilt Steering Wheel	
Mid PTO	×
Fold Down ROPS	
Glow Plug Engine Pre- heat	

04/11/2020 Page 1



Cruise Control	
Horn	•

Loader Attachment

Loader Model #	FL8
Loader Lift Height	8' 4"
Lift Capacity @ 500mm ahead of bkt pivot	1,389 lb
Bucket Width	5' 0"
Loader control valve and joystick	

Compatible Attachments

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.

04/11/2020 Page 2