

AGRIMAXX

- Hydraulic wings
- Hydraulic angle
- Subframe



STD
STANDARD

AGRIMAXX

Snow plow with hydraulic wings and angle. The AgriMaxx pusher is installed in front of a tractor with a Universal Subframe exclusive to Metal Pless.

TECHNICAL SHEET



SCAN ME with your camera application on any phone

AGRIMAXX

Available in STD, HD or LE

Includes angular system and tractor subframe.

This system requires 4 sets of oil outlets.

Not included: hydraulic hoses from the blade to the tractor.

MODEL	BLADE DIMENSIONS			APPLICATION	APPROX. WEIGHT
	BOX	HEIGHT	EXTENDED		
AGLT 0527-10 STD	5'	27"	10'	40-50 HP	982 lbs
AGLT 0627-11 STD	6'	27"	11'	50-60 HP	1 100 lbs
AGLT 0727-12 STD	7'	27"	12'	50-70 HP	1 165 lbs
AGH 0630-11 STD or HD	6'	30"	11'	65-80 HP	1 446 lbs
AGH 0730-12 STD or HD	7'	30"	12'	65-80 HP	1 501 lbs
AGH 0830-13 STD, HD or LE	8'	30"	13'	70-80 HP	1 556 lbs
AGH 0736-13 HD or LE	7'	36"	13'	60-90 HP	1 868 lbs
AGH 0836-14 STD, HD or LE	8'	36"	14'	80-100 HP	2 11 lbs
AGH 0936-15 STD, HD or LE	9'	36"	15'	90-125 HP	2 100 lbs
* AGH 0836-16 HD or LE	8'	36"	16'	90-125 HP	2 200 lbs
AGH 1036-16 STD, HD or LE	10'	36"	16'	100-125 HP	2 188 lbs
AGH 1236-18 STD, HD or LE	12'	36"	18'	100-125 HP	2 380 lbs
AGH 0842-15 HD or LE	8'	42"	15'	125 HP and up	2 427 lbs
* AGH 0842-16 HD or LE	8'	42"	16'	125 HP and up	2 502 lbs
AGH 1042-17 HD or LE	10'	42"	17'	125 HP and up	2 582 lbs
AGH 1242-19 STD, HD or LE	12'	42"	19'	125 HP and up	2 768 lbs

* With subframe MKS2P.

Prices, specs, models and/or model numbers are subject to change.



LE
LIVE EDGE




HD
SOFT DRIVE TRIP EDGE

OPTIONS (not included)

- Tire saver (PPLT or PP).
- Nitrogen accumulator package installed on the lift cylinder (AAC).
- Electric hydraulic diverter valve 4 sets of oil outlets 12 volts (DVDE3 or DVDE4) 13 or 24 GPM to be specified.
- Non standard color (NSC1).
- 3 point hitch attachment (A3P, A3PGF or A3PGB).
- Curb runners (CR...).
- 3/4" x 6" teflon cutting edge (TCE3/4).
- Carbide cutting edge (CCE).
- Electric valve and joystick (JSC4): electric over hydraulic 4 spools mounted on blade with electric control and necessary cable for the installation in the tractor cab.

BLADE POSITIONS



The width of the blade does not determine the real dimension of the product. Pictures shown might have some options.