

PLOWMAXX JR

- Hydraulic angle



PLOWMAXX JR

Snow plow with hydraulic angle. The PlowMaxx JR can be installed on a skid steer, backhoe or wheel loader.

TECHNICAL SHEET



SCAN ME with your camera application on any phone

PLOWMAXX JR



STD
STANDARD



Available in STD, HD or LE

This system requires 1 set of oil outlets.

Not included: - hydraulic hoses from the blade to the vehicle.
- quick coupler


MODEL	BLADE DIMENSION		APPLICATION	APPROX. WEIGHT
	WIDTH	HEIGHT		
PLJR 527 STD	5'	27"	30-40 HP	460 lbs
PLJR 627 STD	6'	27"	30-50 HP	500 lbs
PLJR 727 STD	7'	27"	40-60 HP	560 lbs
PLJR 827 STD	8'	27"	50-70 HP	635 lbs
<hr/>				
PLSO 730 STD	7'	30"	60-70 HP	925 lbs
PLSO 830 STD	8'	30"	70-80 HP	975 lbs
PLSO 930 STD	9'	30"	80-90 HP	1 025 lbs
<hr/>				
PLSO 1036 STD, HD or LE	10'	36"	80-100 HP	1 650 lbs
PLSO 1236 STD, HD or LE	12'	36"	100 HP and up	1 950 lbs
<hr/>				
PLSO 1242 STD, HD or LE	12'	42"	125 HP and up	2 375 lbs

Prices, specs, models and/or model numbers are subject to change.

OPTIONS (not included)

- Teflon cutting edge 3/4" x 6" (TCE%).
- Carbide cutting edge (CCE).
- Non standard color (NSC1).
- Quick coupler.

BLADE POSITIONS



ALSO AVAILABLE



LE
LIVE EDGE



HD
SOFT DRIVE TRIP EDGE

The width of the blade does not determine the real dimension of the product. Pictures shown might have some options.