

REVERSEMAXX

- Hydraulic wings



REVERSEMAXX

Snow plow with hydraulic wings.

The ReverseMaxx is installed on an agricultural loader "arms", skid steer or backhoe.

TECHNICAL SHEET



SCAN ME
with your camera application on any phone

REVERSEMAXX



LE
LIVE EDGE



STD
STANDARD

Available in STD, HD or LE

This system requires 1 set of oil outlets.

Not included: - hydraulic hoses from the blade to the vehicle.
- quick coupler

| MODEL | BLADE DIMENSIONS | | | APPLICATION | APPROX. WEIGHT | |
|---------------|------------------|--------|----------|-------------|----------------|-----------|
| | BOX | HEIGHT | EXTENDED | | | |
| REVLT 0527-10 | STD | 5' | 27" | 10' | 35-45 HP | 1 000 lbs |
| REVLT 0627-11 | STD | 6' | 27" | 11' | 45-55 HP | 1 130 lbs |
| REVLT 0727-12 | STD | 7' | 27" | 12' | 55-65 HP | 1 185 lbs |
| REVM 0630-11 | STD or LE | 6' | 30" | 11' | 50-60 HP | 1 398 lbs |
| REVM 0730-12 | STD or HD | 7' | 30" | 12' | 60-80 HP | 1 498 lbs |
| REVM 0830-13 | STD, HD or LE | 8' | 30" | 13' | 70-90 HP | 1 688 lbs |
| REVM 0736-13 | HD or LE | 7' | 36" | 13' | 60-90 HP | 1 865 lbs |
| REVM 0836-14 | HD or LE | 8' | 36" | 14' | 80-100 HP | 2 000 lbs |
| REVM 0936-15 | STD, HD or LE | 9' | 36" | 15' | 90-125 HP | 2 100 lbs |
| REVM 0836-16 | STD, HD or LE | 8' | 36" | 16' | 85-125 HP | 2 200 lbs |
| REVM 1036-16 | STD, HD or LE | 10' | 36" | 16' | 100-125 HP | 2 185 lbs |
| REVM 1236-18 | STD, HD or LE | 12' | 36" | 18' | 125 HP and up | 2 378 lbs |

Prices, specs, models and/or model numbers are subject to change.

OPTIONS (not included)


- Quick coupler.
- Carbide cutting edge (CCE).
- Teflon cutting edge 3/4" x 6" (TCE3/4).
- Non standard color (NSC1).

ALSO AVAILABLE



HD
SOFT DRIVE TRIP EDGE

BLADE POSITIONS



The width of the blade does not determine the real dimension of the product. Pictures shown might have some options.