

RUBBERMAXX

- Hydraulic wings
- Hydraulic angle (optional)



RUBBERMAXX

Snow plow with rubber cutting edge. It can be installed with or without angulation.

The RubberMaxx can be installed on agricultural loader "arms", skid steer, backhoe or on the front of a tractor with a Universal Subframe exclusive to Metal Pless.

TECHNICAL SHEET



SCAN ME
with your camera application on any phone

RUBBERMAXX



RB
RUBBER EDGE



Available in RB only

This system requires 1 or 4 sets of oil outlets.
Not included: - hydraulic hoses from the blade to the vehicle.
- quick coupler

| MODEL | BLADE DIMENSIONS | | | APPLICATION | APPROX. WEIGHT |
|---------------------------|------------------|--------|----------|-------------|----------------|
| | BOX | HEIGHT | EXTENDED | | |
| RBX 0626-11 ^{RB} | 6' | 26" | 11' | 40-60 HP | 900 lbs |
| RBX 0730-13 ^{RB} | 7' | 30" | 13' | 50-80 HP | 1 350 lbs |
| RBX 0736-14 ^{RB} | 7' | 36" | 14' | 60-90 HP | 1 450 lbs |
| RBX 0836-15 ^{RB} | 8' | 36" | 15' | 90-125 HP | 1 550 lbs |

Prices, specs, models and/or model numbers are subject to change.


Available in:

- Without angulation (**ReverseMaxx**) includes DVDE2, 12 volts, 13 GPM.
- With angulation (**PlowMaxx**) includes DVDE3, 12 volts, 13 GPM.
- With angulation and subframe (**AgriMaxx**).

OPTIONS (not included)

- Quick coupler.
- Nitrogen accumulator package installed on the lift cylinder (**AAC**) (**AgriMaxx**).
- Non standard color (**NSC1**).
- 3 point hitch attachment (**A3P**).
- Electric hydraulic diverter valve 12 or 24 volts (**DVDE3**) 24 GPM maximum capacity, **Bobcat 7 pins**.

BLADE POSITIONS



The width of the blade does not determine the real dimension of the product. Pictures shown might have some options.