

Bobcat CT1025 HST

Engine

Emissions Tier (EPA)	Tier 4
Horsepower	24.5 hp
Displacement	61 in ³
Number of Cylinders	3
Gross HP	24.5 hp
Engine Model	3C100LFH- U1
RPM	3400

Performance

Operating Weight	1,521 lb
Travel Speed	11 mph
Travel Speed - Reverse	7.5 mph
3- Point Hitch	Category 1
3- pt Lift Control Type	Hydraulic Position Control System
Lift Capacity at 24" behind Lift Point	700 lb
Rear PTO System	Independent
Rear PTO - RPM	540
PTO HP	18.8 hp
Mid PTO - RPM	2200

Capacities

Fuel Tank	6.7 gal

Hydraulic System

Total Hydraulic Flow	7.2 gal/ min

Drive System

Brake Type	We Multi Disc
Transmission Type	Infinite, 2 RangeHydrostatic

Dimension

Length	99.3 in
Width	46 in
Height	87.6 in
Ground Clearance	6.3 in
Turning Radius	8' 3"
Wheelbase	4' 7"
Front Tire Size	Front AG. (TURF, INDUSTRIAL) 18X8.5-10(18X8.5-10)
Rear Tire Size	Rear AG. (TURF, INDUSTRIAL) 26X12.00-12(26X12.00-12)

Loader Attachment

Loader Lift Height	6' 0"
Lift Capacity @ 500mm ahead of bkt pivot	702 lb
Bucket Width	4' 0"

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.