

Engine

Emissions Tier (EPA)	Tier 4
Engine Make	Daedong
Horsepower	24.5 hp
Displacement	100 in ³
Number of Cylinders	3
Gross HP	24.5 hp
Engine Model	3A165LWM(H)
RPM	2600

Performance

Operating Weight	2,634 lb
Travel Speed	9.5 mph
Travel Speed - Reverse	8.5 mph
3- Point Hitch	Category 1
3- pt Lift Control Type	Hydraulic Position Control System
Lift Capacity at 24" behind Lift Point	1,631 lb
Rear PTO System	Live
Rear PTO - RPM	540
PTO HP	21.8 hp
Mid PTO - RPM	1976

Capacities

Fuel Tank	9 gal
-----------	-------

Hydraulic System

Total Hydraulic Flow	11.4 gal/ min
----------------------	---------------

Drive System

Number of Forward Speeds	3
Brake Type	Wet Multi Disc
Transmission Type	Infinite, 3 RangeHydrostatic
Traction System	4x4

General

Contract Codes	Compact Utility Tractor
First Year of Production	2019

Dimension

Length	120.9 in
Width	64 in
Height	91.5 in
Ground Clearance	11.5 in
Turning Radius	8' 0"
Wheelbase	5' 5"
Front Tire Size	Front AG. (TURF, INDUSTRIAL) 7-16 (28 x 8.5-15/6, 27X8.5-15)
Rear Tire Size	Rear AG. (TURF, INDUSTRIAL) 11.2-24 (41 x 14-20/4, 15-19.5)

Features

Suspension Seat	■
Spark Arrestor Muffler	Standard
Tilt Steering Wheel	□
Mid PTO	×
Fold Down ROPS	■
Glow Plug Engine Pre- heat	■



Cruise Control	×
Horn	■

Loader Attachment

Loader Model #	FL7
Loader Lift Height	7' 10"
Lift Capacity @ 500mm ahead of bkt pivot	1,369 lb
Bucket Width	5' 0"
Loader control valve and joystick	■

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.