

Bobcat CT5558 E HST

Engine

Emissions Tier (EPA)	Tier 4
Engine Make	Daedong
Horsepower	57.7 hp
Displacement	111 in³
Number of Cylinders	3
Gross HP	57.7 hp
Engine Model	3FT- TH4- U
RPM	2750

Performance

Operating Weight	4,685 lb
Travel Speed	17.5 mph
Travel Speed - Reverse	17.5 mph
3- Point Hitch	Category 1
3- pt Lift Control Type	Position with Draft Control
Lift Capacity at 24" behind Lift Point	3,177 lb
Rear PTO System	Independent
Rear PTO - RPM	540
PTO HP	48.3 hp
Mid PTO - RPM	2103

Capacities

Hydraulic System

Implement Hydraulic Flow	14 gal/ min
Total Hydraulic Flow	17.8 gal/ min
Steering Hydraulic Flow	12 gal/ min

Drive System

Number of Forward Speeds	3
Brake Type	Wet Multi Disc
Transmission Type	Infinite, 3 RangeHydrostatic (Servo control valve with Electric sol.)
Traction System	4x4

General

Contract Codes	Compact Utility Tractor
First Year of Production	2019

Dimension

Length	139.6 in
Width	75 in
Height	94.2 in
Ground Clearance	13 in
Turning Radius	9' 9"
Outside Turning Diameter	20' 1"
Wheelbase	6' 3"
Front Tire Size	Front AG. (TURF, INDUSTRIAL) '9.5-16(29-12.5-15, 10-16.5)
Rear Tire Size	Rear AG. (TURF, INDUSTRIAL) '13.6-28(21.5L-16.1, 17.5-24)

Features

Suspension Seat	•
Spark Arrestor Muffler	Standard
Tilt Steering Wheel	•
Mid PTO	×

28/09/2021 Page 1



Fold Down ROPS	
Glow Plug Engine Pre- heat	•
Cruise Control	
Horn	

Loader Attachment

Loader Model #	FL9-5
Loader Lift Height	9' 1"
Lift Capacity @ 500mm ahead of bkt pivot	2,346 lb
Bucket Width	6' 0"
Loader control valve and joystick	

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.

28/09/2021 Page 2