

Engine

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	74 hp
Turbocharged Engine	×

Performance

Rated Operating Capacity (ISO)	2,450 lb
Operating Capacity (50% of Tip)	3500 lb
Tipping Load	7000 lb
Operating Weight	8927 lb
Travel Speed	7.2 mph
Travel Speed (2- speed option)	10.2 mph
Ground Pressure (Rubber)	5.9 psi

Capacities

Fuel Tank	28.3 gal
-----------	----------

Hydraulic System

System Relief @ Quick Couplers	3,500 psi
Auxiliary Std Flow	17.6 gal/ min
Auxiliary High Flow	26.9 gal/ min

Dimension

Length	134.9 in
Length without Attachment	107 in
Length with Standard Bucket	134.9 in
Width	67 in
Width (with bucket)	68 in
Height	80.5 in
Height with Operator Cab	80.5 in
Height to Bucket Hinge Pin	120 in
Reach @ Maximum Height	36.7 in
Turning Radius	81.5 in
Length of track on ground	54.3 in
Track Width	12.6 in
Track Width - Optional	15.7 in

Features

Joystick Control	×
Air Conditioning	×
Backup Alarm	■
BICS System (Interlock)	■
Cab Heater	×
Operating Lights	■
Suspension Seat	■
Two Speed Travel	×
Deluxe Instrumentation	×
Engine Shutdown	□
Hydraulic Bucket Positioning	×
High Flow Option	×
Auxiliary Hydraulics	■
Bob- Tach Attachment System *	■
Power Bob- Tach *	×

ACS (Switchable Controls)	<input type="checkbox"/>
Ride Control	×
Horn	■

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.