



Bobcat T740

Configuration	Standard	Roller Suspension Option
---------------	----------	--------------------------

Engine

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	74 hp
Turbocharged Engine	×
Engine Model	3.4L Bobcat Engine
Engine Make	Bobcat
Displacement	208 in ³
Torque RPM	1,400 rpm
Number of Cylinders	4

Performance

Rated Operating Capacity (ISO)	3,310 lb
Operating Capacity (50% of Tip)	4571 lb
Rated Operating Capacity (35% Of Tip)	3200 lb
Tipping Load	9143 lb
Operating Weight	10127 lb
Travel Speed	6 mph
Travel Speed (2- speed option)	8.3 mph
Ground Pressure (Rubber)	4.1 psi

Capacities

Fuel Tank	43.8 gal
-----------	----------

Hydraulic System

System Relief @ Quick Couplers	3,500 psi
Auxiliary Std Flow	23 gal/ min
Auxiliary High Flow	30.5 gal/ min

General

Contract Codes	Compact Track Loader
First Year of Production	2015

Controls

Hydraulic (Lift and Tilt)	Dual Pedals
Control Option	Selectable Joystick Controls (SJC)
Auxiliary Hydraulics Type	Fingertip Controls

Dimension

Length	114.3 in
Length without Attachment	114.3 in
Length with Standard Bucket	141.6 in
Width	78 in
Width (with bucket)	80 in
Height	81.3 in
Height with Operator Cab	81.3 in
Height to Bucket Hinge Pin	131 in
Reach @ Maximum Height	35.2 in
Turning Radius	88 in
Length of track on ground	63.7 in
Track Width	17.7 in
Track Width - Optional	12.6 in
Ground Clearance	9.4 in

Dump Angle @ Maximum Height	37°
-----------------------------	-----

Features

Joystick Control	×
Air Conditioning	×
Backup Alarm	■
BICS System (Interlock)	■
Cab Heater	×
Operating Lights	■
Suspension Seat	■
Two Speed Travel	×
Deluxe Instrumentation	×
Engine Shutdown	■
Hydraulic Bucket Positioning	×
High Flow Option	×
Auxiliary Hydraulics	■
Bob- Tach Attachment System *	■
Power Bob- Tach *	×
ACS (Switchable Controls)	□
Ride Control	×
Horn	■

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.