

Bobcat T770

Configuration	Standard	Roller Suspension Option
---------------	----------	--------------------------

Engine

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	92 hp
Turbocharged Engine	×

Performance

Rated Operating Capacity (ISO)	3,475 lb
Operating Capacity (50% of Tip)	4960 lb
Tipping Load	9929 lb
Operating Weight	10515 lb
Travel Speed	6.6 mph
Travel Speed (2- speed option)	10.7 mph
Ground Pressure (Rubber)	4.2 psi

Capacities

Fuel Tank	43.8 gal
-----------	----------

Hydraulic System

System Relief @ Quick Couplers	3,500 psi
Auxiliary Std Flow	23 gal/ min
Auxiliary High Flow	36.6 gal/ min

Dimension

Length	141.6 in
Length without Attachment	114.3 in
Length with Standard Bucket	141.6 in
Width	78 in
Width (with bucket)	80 in
Height	81.3 in
Height with Operator Cab	81.3 in
Height to Bucket Hinge Pin	131.4 in
Reach @ Maximum Height	35.2 in
Turning Radius	88 in
Length of track on ground	63.7 in
Track Width	17.7 in

Features

Joystick Control	×
Air Conditioning	×
Backup Alarm	■
BICS System (Interlock)	■
Cab Heater	×
Operating Lights	■
Suspension Seat	■
Two Speed Travel	×
Deluxe Instrumentation	×
Engine Shutdown	■
Hydraulic Bucket Positioning	×
High Flow Option	×
Auxiliary Hydraulics	■
Bob- Tach Attachment System *	■

Power Bob- Tach *	×
ACS (Switchable Controls)	×
Ride Control	×
Horn	■

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.